

GRABO H - HEAVY LIFTING MADE EASY





Specifications:

Model/SKU	GRABO H / NGH-1B
Battery	11.1VDC 2000mAh Li-ion
Rated Power	16W
Charger Input Voltage	100-240VAC 50/60Hz
Battery Charging Time	~2hrs
Non-Stop Running Time (Full Charge)	1hrs
Running Cycles (On Full Charge)	340 ON-OFF cycles of 10 seconds
Stand-by Mode (Charge Hold)	25 days
Pump Service Life	100000+ ON-OFF cycles / 800+ hrs continuous
Rated Air Flow	0.5cfm (15 L/min)
Maximum Vacuum Rate	11.6Psi (0.8 Bar, 80 kPa)
Maximum Lifting Capacity	330Lbs (150 kg)
LxWxH	11.67 x 7.12 x 4.76" (297 x 181 x 121 mm)
Net Weight (With Battery)	2.6Lbs (1.2kg)
Working Temperature	32°F~140°F (0°~60 °C)
Applicable Surface Type	Peak/valley heights less than 0.1" (3mm), arc less than 5°

Lifting Capacity:

Material Direction	Glass	Ceramic Tiles	Metal	Plastic	Wood	Rough Slate	Rough Concrete	Dry Wall	
Perpendicular Hold	330Lbs (150 kg)	330Lbs (150 kg)	242Lbs (110 kg)	220Lbs (100 kg)	176Lbs (80 kg)	176Lbs (80 kg)	176Lbs (80 kg)	132Lbs (60 kg)	
Parallel Hold	220Lbs (100 kg)	220Lbs (100 kg)	176Lbs (80 kg)	176Lbs (80 kg)	132Lbs (60 kg)	132Lbs (60 kg)	132Lbs (60 kg)	88Lbs (40 kg)	

Based on product information at time of publication. Environmental conditions can affect product performance and longevity; consult the product manual on GRABO.com or contact a Sales Representative for more information.

By Nemo Power Tools - www.GRABO.com

GRABO headquarters:

Eastern Commerce Center 6000 S Eastern Ave Unit 8B Las Vegas, Nevada, 89119

Info@GRABO.com

www.GRABO.com

Main Office: +1 (844) 430-0510

Help & Warranty: +1 (702) 718-2433